

Included Hardware:

(8-Bolt)

- (10) 1/4" x 1 1/4" (SS) Self drill screws
- (10) #10 washers
- (2) (SSBO) washers
- (2) SS flange nuts
- (2) 1/4-20 x 1" bolts (SSBO)
- (2) **twist brackets #10008**

Tools Needed:

- drill
- 1/8" drill bit
- locking pliers
- Small level
- 5/16" drill bit
- clamps
- 3/8 socket on drill attachment for self-drilling screws.

Installation Steps:

1. PARK VEHICLE ON LEVEL WORK AREA.
2. Unpack and verify all parts are included per list above. **If anything is missing, please call DuraFlap at the number below.**
3. Position the mud flap with the grooved side toward the tire. Secure it with a clamp.
 - a. Line up the mud flap centered on the tire.
 - b. Adjust height. **DuraFlap recommends 7 to 9" off the ground.**

NOTE: On rear mud flaps, ensure clearance of at least 3" between your tailpipe and the mud flap.

4. Double check mud flap is square and plumb to the tires.
5. Drill one 1/8" hole through the mud flap and wheel well lip at the upper outside corner.
 - a. Secure it with a self-tapping screw thru the washer, mud flap and into the fender lip. Leave slightly loose for now.
6. Place the level to the outside edge of the mud flap and adjust for vertical plumb.
7. Drill the second hole in the bottom outside edge of the mud flap and wheel well lip and secure with a second screw or bolt. If using a bolt, the pre-drilled hole will need to be 5/16".
8. Align the twist bracket as shown in image:
9. Pre-drill a 1/8" hole in the rocker panel where the bracket lines up.

NOTE: Be careful to drill the hole within 1" of the bottom of the panel to make sure it does not penetrate the outside of the van.

10. Attach the bracket to the rocker panel with the self-tapping screw. Attach it to the mud flap with the SS bolt, nut and washer. Adjust bracket as necessary.
11. Install the remaining screws, evenly spaced and tighten all screw/bolts.

NOTE: Check bolts and screws for tightness every three months.

Replace moisture in the mud flap by applying furniture polish, vinyl or leather treatment or other moisturizer twice a year.



If you have any questions, give us a call. (541) 245-9148